

SecureTouch Surface Wave

For High-Threat Indoor Environments



Elo's SecureTouch touchscreens are the preferred touch solution for high-threat environments and indoor applications demanding rugged durability. SecureTouch touchscreens deliver high impact resistance; the durable screen comes in fully tempered, heat or chemically strengthened glass that continues to work even if scratched. With their stable, drift-free operation, the SecureTouch touchscreens are well suited for high usage environments and provides a touch response that is accurate. SecureTouch touchscreens are the ideal touch solution for kiosks in high-threat indoor environments, ticketing machines, interactive pay phones, and gaming machines.

Benefits

- High impact resistance
- Continues to work even if scratched
- Stable, drift-free operation
- 10-year limited warranty

Applications

- Kiosks in high-threat environments
- Ticketing machines
- Interactive pay phones
- Gaming machines

SecureTouch Surface Wave Specifications

MECHANICAL

Input Method	Finger or gloved hand (cloth, leather, or rubber) activation
Available Sizes	10.4" to 21"; visit our Web site for full specifications and other offerings

ELECTRICAL

Positional Accuracy	Standard deviation of error is less than 0.080 in. (2 mm)
Resolution	Touchpoint density is based on controller resolution of 4096 x 4096, plus 255 levels corresponding to touch pressure
Touch Activation Force	Typically 2 to 3 ounces (55 to 85 grams)
Controller	Board: Serial (RS232) or USB 1.1

OPTICAL

Light Transmission	Up to 90% per ASTM D 1003-92
--------------------	------------------------------

ENVIRONMENTAL

Temperature	Operating: -20°C to 50°C Storage: -40°C to 71°C
Relative Humidity	Operating: 40°C at 90% RH, noncondensing
Altitude	Operating: 10,000 ft (3,048 m) Storage/transport: 50,000 ft (15,240 m)
Chemical Resistance	The touch active area of the touchscreen is resistant to chemicals that do not affect glass, such as: acetone, toluene, methyl ethyl ketone, isopropyl alcohol, methyl alcohol, ethyl acetate, ammonia-based glass cleaners, gasoline, kerosene, vinegar
Electrostatic Protection	Per EN 6100-4-2, 1995: Meets Level 4 (15 kV air/8 kV contact discharges)
Agency Approvals	UL, cUL, TÜV, CE, FCC Class A
Sealability	Can be sealed to meet NEMA 3/3R/5/12/12K/13, IP64 standards

DURABILITY

Surface Durability	Surface durability is that of glass. Mohs' hardness rating of 7
Expected Life	No known wear-out mechanism, as there are no layers, coatings, or moving parts. SecureTouch technology has been operationally tested to more than 50 million touches in one location without failure, using a stylus similar to a finger.
Impact Resistance	Meets UL-60950 and CSA 22.2 No. 60950 ball drop test (0.5 kg, 50 mm diameter ball dropped from height of 1.3 m)
Warranty	Touchscreen: 10-year limited warranty Controller: 5-year limited warranty



2701 dual serial/USB controller