



## 8" Rimless POS LCD Monitor



### Features

1. Rimless front bezel design
2. Integrated with protection glass (Model: P080UG) or 5 wires resistive flat touch (Model: P080UR)
3. Small footprint
4. VESA 75 x 75 mm wall mounting standard
5. User friendly OSD control buttons
6. Sleek surface throughout monitor's appearance
7. Optional tool-free height adjustment pole base (Patent No.: M433068)
8. Smart cable management
9. Viewing angle adjustment up to 120° (L/R) / 30° (upward)
10. Low power consumption only 2.5W with LED backlight

### Specification

Model	P080UG / P080UR
Cabinet Color	Black x White
Cover Lens	Mitsubishi PMMA Hardness > 5H (JIS D0202), T > 93% (Model: P080UG) 5 wires resistive flat touch (Model: P080UR)
Display Type	8" diagonal TFT active matrix with LED backlight
Recommended Resolution	800 x 600
Brightness	250 cd/m <sup>2</sup> (typ.)
Contrast Ratio	500:1 (typ.)
Viewing Angle	125° (H) / 140° (V)
I/O Connectivity	Mini USB

\* Specification is subject to be changed without prior notice.

**Applications:** Supermarket/Chain stores  
Hospitality/Factory automation



### Dimension (unit: mm)

